

American Ultraviolet

AUV-Coat UV Coater

25, 30 & 36" UV and Aqueous Coater Systems (Hand Fed or with Feeder)



FEATURES:

- High speed UV/AQ coating solution for digital prints or offset output
- User-friendly touch screen control panel
- One side metering roller and rubber roller adjustment
- Dual ridged polymer doctor blade for bottom roller cleanup
- Full recirculation fluid pumping system
- Vacuum hold-down throughout conveyor paper path
- High output UV/IR drying systems
- Run up to 3/8" thick substrate (without feeder)
- Optional automatic vacuum feeder and receding stacker

Heavy Duty
Industrial
Construction

Technical Specifications

Model Number: **AUV-Coat 25"**
Max Sheet Size: 24" x 30" with Feeder
Min Sheet Thickness: 100 lb Text
Max Speed w/Max Sheet Size: 4,500 SPH
Equipment Dimensions: 149"(L) x 46"(W) x 45"(H)
Power Requirements: 208-240V, 3PHS, 65AMP w/Neutral (add 10AMPS w/Stacker)

Model Number: **AUV-Coat 30"**
Max Sheet Size: 30" x 40" with Feeder
Min Sheet Thickness: 100 lb Text
Max Speed w/Max Sheet Size: 4,000 SPH
Equipment Dimensions: 172"(L) x 54"(W) x 45"(H)
Power Requirements: 208-240V, 3PHS, 75AMP w/Neutral (add 10AMPS w/Stacker)

Model Number: **AUV-Coat 36"**
Max Sheet Size: 36" x 30" with Feeder
Min Sheet Thickness: 100 lb Text
Max Speed w/Max Sheet Size: 4,000 SPH
Equipment Dimensions: 165" (L) x 57" (W) x 45" (H)
Power Requirements: 208-240V, 1PHS 60HZ 100 AMPS Service (add 10 AMPS w/Stacker)

American Ultraviolet
Corporate Headquarters
212 South Mt. Zion Road
Lebanon, IN 46052
(765) 483-9514 • (800) 288-9288
Fax: (765) 483-9525

American Ultraviolet Coatings, Inc.
23555 Telo Avenue
Torrance, CA 90505
(310) 784-2930
(800) 615-3726



American Ultraviolet®

Since 1960. It's all we do.

www.americanultraviolet.com

Printed With:



UV Coating Solutions

